

PRODUCT NAME: BWTS45 DATE ISSUE: 16 JUNE 2020 REFERENCE NO: VERSION 20.02 REPLACES: 13 JULY 2016

PRODUCT IDENTIFIER: BTWS45 SUPPLIER NAME: UDS PTY LTD ADDRESS: 3 SPIRETON PLACE

PENDLE HILL NSW 2145
TELEPHONE: 02 9688 2022

RECOMMENDED USE: A BOILER WATER PRODUCT FOR CORROSION

AND SCALE CONTROL

2. HAZARD IDENTIFICATION

Classification of the Classified as Hazardous according to the criteria of GHS. substance or mixture Classified as Dangerous Goods according to ADG Code.

This material is classified as HAZARDOUS according to the criteria of Safe Work

Australia. Classification:

Acute Toxicity (Oral) – Category 4 Skin Corrosion – Category 1A Eye Damage – Category 1

Signal Word(s) Danger Hazard Statement(s) H302

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

Pictogram(s)

Precautionary Statement

Prevention

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves/protective clothing/eye

protection/face protection.

Precautionary Statement

– Response

P363 Wash contaminated clothing before reuse.

P301+P312 IF SWALLOWED: Call a POISON C

IF SWALLOWED: Call a P doctor/physician If you feel unwell.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse SKIN with water/shower.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in

a position comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Precautionary Statement

Storage

P405

05 Store locked up.

Precautionary Statement

– Disposal

P501

Dispose of contents/container to an approved waste

disposal plant.

Other Information Some individuals are said to be dangerously sensitive to minute amounts of

PRODUCT NAME: BWTS45 DATE ISSUE: 16 JUNE 2020 REPLACES: 13 JULY 2016 REFERENCE NO: VERSION 20.02

> sulphites in foods and some bronchodilator medicines preserved with sulphites. Symptoms may include bronchoconstriction, shock, gastrointestinal disturbances, angio oedema, flushing and tingling sensations.

COMPOSITION/INFORMATION ON INGREDIENTS

Composition Ingredients	Name	CAS	Proportion	
	Potassium Hydroxide	1310-58-3	10-30 %	
	Acrylic Polymer	Propriety information	1-10 %	
	Sodium Sulphite	7757-83-7	10-30 %	
	Water	7732-18-5	30-60 %	

FIRST AID MEASURES

Remove the source of contamination or move the victim to fresh air. If Inhalation

> breathing is difficult, ensure airways are clear and have qualified person give oxygen through a face mask. If symptoms develop, seek medical attention.

Ingestion If swallowed, give 2 glasses of water to drink. IMMEDIATELY call a physician.

Never give anything by mouth to an unconscious person.

Skin Wash affected skin areas thoroughly with soap and water. Remove and wash

contaminated clothing thoroughly. DO NOT take clothing home to be laundered. Discard contaminated shoes, belts and other articles made of

leather. Get prompt medical attention.

Eye Contact IMMEDIATELY flush eye(s) copious amount of water for approximately 15

minutes holding eyelid(s) open. Take care not to rinse contaminated water

into the non-affected eye. Seek immediate medical attention.

Advice to Doctor MATERIAL IS CORROSIVE. Mucosal damage may contraindicate the use of

gastric lavage.

FIRE-FIGHTING MEASURES

Suitable Extinguishing

Water, foam, carbon dioxide or dry chemical

Hazard from Combustion

Products

Media

Product is non-flammable.

Specific Hazards Combustion products - Carbon dioxide, carbon monoxide and oxides of

phosphorus and sulphur

Fire-fighters use Self-Contained Breathing Apparatus (SCBA) Precautions

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures

Personal Protection: Wear an AS1716 approved (or equivalent) positive pressure self-contained breathing apparatus or a full-face piece airline respirator in the positive pressure mode with emergency escape provisions. Wear compatible, chemically resistant gloves. MATERIAL IS CORROSIVE. If exposed to material during clean-up operations IMMEDIATELY remove all contaminated clothing and wash exposed skin areas with soap and water. See FIRST AID PROCEDURES Section for further information. Protective clothing made of the following material should be worn to avoid skin contact: Plastic rain jackets and pants.

Butyl rubber, Nitrile or PVC

Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when



PRODUCT NAME: BWTS45 REFERENCE NO: VERSION 20.02

possible.

Clean-up & Disposal Collect liquid in an appropriate container or absorb with an inert material

(e.g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible material, such as saw dust. Wash residue to sewer. For large spills, confirm with appropriate water authority. Discharge, treatment and disposal may be subject to federal, state or local laws and

DATE ISSUE: 16 JUNE 2020

REPLACES: 13 JULY 2016

these should be consulted before discharge.

7. HANDLING AND STORAGE

Safe Handling Safe Storage In use avoid contact with chemical listed as hazardous reactions.

Store away from oxidising agents and acids. Store in a dry place avoiding iron containers. Keep in a cool dry place (0 to 30 °C). Keep away from sources of ignition. Freezing will affect the physical condition and may

damage the material.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National Exposure Standards Use local exhaust if misting occurs. Natural ventilation is adequate in the absence of mists. Exposure standards for the decomposition products are:

Material	TWA	STEL
Potassium Hydroxide (dust)	2 mg/m ³	12 hrs peak
		limitation

The measures appropriate for a particular worksite depend on how this material is used and on the extent of exposure. Use this general information to help develop specific control measures. Ensure that control systems are properly designed and maintained and comply with occupational, environmental, fire, and other applicable regulations.

Biological Limit Values Engineering Controls No biological limit allocated.

A system of local and/or general exhaust is recommended to keep employee exposures as low as possible. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Adequate ventilation should be provided so that exposure limits are not exceeded.

Respiratory Protection

Eve Protection

If engineering controls are not effective in controlling airborne exposure, then a half face piece respirator with a replaceable organic vapour filter should be used. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Safety glasses or goggles should be worn as described in Australian Standard

AS/ANZ 1337, Eye Protectors for Industrial Applications.

Not decrease as sinilar decrease and decrease as a second control of the second control

Hand Protection

Butyl, neoprene or nitrile gloves are recommended when using this product.

Suitable workwear should be worn to protect personal clothing. When large quantities are handled, the use of plastic aprons and rubber boots is

recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Clear pale amber liquid
Boiling Point Approximately 100 °C
Melting Point Not applicable
Solubility in Water Soluble

PRODUCT NAME: BWTS45 DATE ISSUE: 16 JUNE 2020 REFERENCE NO: VERSION 20.02 REPLACES: 13 JULY 2016

Specific Gravity 1.10 to 1.30 at 20 °C approximately

pH Value 12.00 to 14.00 Vapour Pressure No data Vapour Density (Air=1) No data Flash Point Does not flash Flammability Does not ignite Not applicable Ignition Temperature Flammable Limits (Lower) Not applicable Flammable Limits (Upper) Not applicable

10. STABILITY AND REACTIVITY

Chemical Stability Stable under normal ambient.

Conditions to Avoid Avoid excessive heat, direct sunlight, generating dust, moisture, static

discharges, open flame and high temperatures.

Incompatible Materials Oxidising materials and acids. May cause exothermic reaction, explosions

and release of toxic gases. Wide variety of materials including many metals, ammonium compounds, cyanides, acids, nitro compounds, phenols,

combustible organics.

Emits toxic gases.

Hazardous Decomposition

Products

11. TOXICOLOGICAL INFORMATION

Will not occur.

Toxicology Information As potassium hydroxide:

Acute oral toxicity rat: LD50, 40 mg/kg.

Acute skin irritation rabbit: LD₅₀, 500 mg/ 24h (severe)

Very corrosive. Causes severe burns.

As sodium sulphite:

Acute oral toxicity rat: LD50, 820 mg/kg.

Inhalation Severe irritant. Effects from inhalation of dust or mist may vary from mild

irritation to serious damage of the upper respiratory tract, depending on severity of exposure. Symptoms may include sneezing, sore throat or runny

nose. Severe pneumonitis may occur.

Ingestion Corrosive! Swallowing may cause severe burns of mouth, throat, and

stomach. Severe scarring of tissue and death may result. Symptoms may

include bleeding, vomiting, diarrhoea, fall in blood pressure.

Although only moderately toxic in large amounts, sulphites can pose risk to some asthmatics producing central nervous system depression, bronchoconstriction and anaphylaxis. Damage may appear days after

exposure.

Skin Corrosive! Contact with skin can cause irritation or severe burns and scarring

with greater exposures.

Eye Eye contact will cause severe burns and permanent eye damage.

Chronic Health Effects Long term exposure may result in dermatitis.

12. ECOLOGICAL INFORMATION

Ecotoxicity No information available on ecotoxicity for this product.

Persistence/Degradability Readily biodegradable.

Mobility No information available on mobility for this product.

Bioaccumulative Potential No information available on bioaccumulation for this product.

PRODUCT NAME: BWTS45 DATE ISSUE: 16 JUNE 2020 REFERENCE NO: VERSION 20.02 REPLACES: 13 JULY 2016

Environmental Protection Do not allow it to enter waterways. The effects of this product on aquatic

organisms are rapidly and significantly mitigated by the presence of

dissolved organic carbon in the aquatic environment.

13. DISPOSAL CONSIDERATIONS

Method Neutralise with 10 % solution of acetic acid or sulphuric solution at pH 7 and

rinse empty containers with water. If pH is lowered below 7, oxides of sulphur gases may be generated. Can be land filled or incinerated, when in compliance with local regulations. For large quantities, notify your local

waste management authority for specific regulations.

14. TRANSPORT INFORMATION

Transport Information Classified as dangerous goods according to the Australian Code for the

Transport of Dangerous Goods by Road and Rail (7th Edition).

UN Number 171

UN Proper Shipping Name CAUSTIC ALKALI LIQUID, N.O.S.

Class 8
Hazchem Group 2R
Packaging Group III

Special Precautions Store in tightly closed containers in a cool area separated from normal work

areas. The storage area should have adequate independent ventilation and have no sources of heat or sparks. DO NOT load with Class 1, 4.2, 5.1, 5.2, 7

or 8.

15. REGULATORY INFORMATION

Poisons Schedule Number Not scheduled.

Packaging and Labelling As required by the ADG Code and Standard for the Uniform Scheduling of

Drugs and Poisons (SUSDP).

The ingredients contained in this product listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Date Prepared 16th June 2020

Abbreviations GHS - Globally Harmonised System of Classification and Labelling of

Chemicals

ADG – Australian code for the Transport of Dangerous Goods by Road and

Rail

TWA – Time Weighted Average STEL – Short Term Exposure Limit

LD₅₀ (Lethal Dose) - Amount of ingested product that kills 50% of a test

sample.

Others This information summarizes our best knowledge of the health and safety

hazard information of the product and how to safely handle and use the product in the workplace. Each user should read this SDS and consider this information in the context of how the product will be handled and used in

the workplace including in conjunction with other products.