

TUMBLE DRYERS

TRD 11 · 16 · 23



STANDARD FEATURES & BENEFITS

- Tumble dryer in skin plate, cream color
- Big loading door (opening of 180°)
- Direct drive through a gearbox, no pulley
- Time and temperature selection
- Reverse drum: all models offer the reverse turning of the drum
- Drum in galvanised steel
- Digital control and electronic control. Easy and intuitive to use, the electronic control offers a complete control of the process
- Radial airflow circuit
- New filter drawer with wide surface and improved airflow, filter grid is standard 0,3 mm
- Cool down: anti-wrinkle at the end of cycle
- Models available in electric, gas or steam heating
- Self-Service: digital range has several payment options for laundromats; to work with centralized payment systems, with coin / token, or with prepay card systems. Electric and gas heated models for self-service available

OPTIONS

- Moisture control
- Double doorglass
- Stainless steel drum with mixed axial-radial flow and punched drum holes
- Stainless steel body
- Stainless steel front panel
- Low pressure steam battery
- Opposite door opening
- Lint filter with dia. 0,6 or 1,2 mm mesh
- Wooden box packing
- Special voltages
- Mechanical meter for coin / token
- Electronic coin kit

TOLON

TUMBLE DRYERS

TRD 11 · 16 · 23

MODEL	UNIT	TRD 11	TRD 16	TRD 23			
Capacity 1/18	kg	12	18	26			
Capacity 1/20	kg	10,5	16,5	23			
Hourly output *	kg/h	28,6	31,9	40,6			
Evaporation capacity *	l/h	14,5	16,3	20,4			
DRUM							
Ø Drum	mm	750	750	855			
Ø Door	mm	574	574	574			
Center door height	mm	976	976	1.030			
Bottom door height	mm	689	689	743			
Drum depth	mm	475	746	800			
Drum volume	l	210	330	460			
POWER							
Drum motor	kW	0,37	0,37	0,37			
Fan motor	kW	0,25	0,25	0,55			
Electric heating	kW	12	18	24			
Total electric power (elec. model)	kW	12,67	18,67	24,97			
Gas heating	kW	20,51	20,51	31			
Steam heating	kW	30	30	49,2			
CONNECTIONS							
		ELECTRICAL - STEAM /GAS		ELECTRICAL - STEAM /GAS		ELECTRICAL - STEAM /GAS	
Tension 230V - I + N + T	No x mm ² / A	3 x 35 / 63A	3 x 1,5 / 20A	-	3 x 1,5 / 20A	-	3 x 1,5 / 20A
Tension 230V - III + T	No x mm ² / A	4 x 10 / 40A	3 x 1,5 / 20A	4 x 16 / 63A	3 x 1,5 / 20A	4 x 25 / 80A	3 x 1,5 / 20A
Tension 400V - III + N + T	No x mm ² / A	5 x 4 / 25A	3 x 1,5 / 20A	5 x 10 / 32A	3 x 1,5 / 20A	5 x 10 / 40A	3 x 1,5 / 20A
Ø Gas inlet	BSP	1/2"		1/2"		1/2"	
Ø Steam inlet	BSP	3/4"		3/4"		1"	
Ø Condensed (Steam models)	BSP	3/4"		3/4"		1"	
DIMENSIONS / PACKING DIMENSIONS							
Net Width / Gross Width	mm	785 / 865		785 / 865		890 / 970	
Net Depth / Gross Depth	mm	840 / 940		1.110 / 1.210		1.245 / 1.345	
Net Height / Gross Height	mm	1.694 / 1.840		1.694 / 1.840		1.812 / 1.940	
Net Weight / Gross Weight	kg	172 / 180		187 / 200		210 / 230	
OTHERS							
Max airflow	m ³ /h	850		850		1.200	
Ø Fume exhaust	mm	200		200		200	
Sound level	dB	64		64		65	

* It may vary depending on the type of heating, filter cleanliness or extraction type.