

WASHER EXTRACTORS

TWE 10 · 15 · 18



STANDARD FEATURES & BENEFITS

- Freestanding, high spin washer
- Compact & modern space-saving design
- Large loading and unloading doors with up to 180° opening angle for easy access
- Choice of liquid and powder detergent in 5 compartment frontal dispenser
- Standard equipped for automatic soap dosing
- Drum and tub, as well as front and top panel made of robust and durable high quality stainless steel AISI 304
- Ceramic coated shaft for longer life due to less friction on sealing surfaces
- Highly flexible and freely programmable control with advanced 7" colour display for easy operation and perfect management of your laundry business
- USB connection for quick data transfer and data editing on simple .csv format
- On screen photographic illustrated troubleshooting guide
- Clear status light indication for easy and quick visual management
- Large 3" drain valve for fast evacuation and shorter cycles
- Accelerometer for perfect balancing
- Water inlet hoses
- Steam inlet hose

OPTIONS

- Dual heating (electric & steam) selectable through the control
- Stainless steel side panels
- Stainless steel back panel
- 3rd inlet valve for soft water
- High flow inlet valves for faster filling
- Pneumatic inlet valves for faster filling
- Pneumatic steam valve
- Chemical hold signal
- Integrated plinth to increase loading height and ensure ergonomic operation and fit linen carts

TOLON

WASHER EXTRACTORS

TWE 10 · 15 · 18

MODEL	UNIT	TWE 10	TWE 15	TWE 18
Dry load	kg	10	15	18
Performance	kg/h	15	22,5	27
Cycle time	min	30-45	30-45	30-45
DRUM				
Drum diameter	mm	630	630	630
Drum depth	mm	330	490	580
Drum volume	l	103	153	181
Wash speed	rpm	43	43	43
Extraction speed	rpm	1012	1012	1012
G-force		360	360	360
DOOR				
Door opening Ø	mm	455	455	455
HEATING				
Electric	kW	9	15	18
Steam	bar	4-6	4-6	4-6
ELECTRIC				
Electric consumption*	kWh	2,34	3,10	3,66
Motor	kW	1,5	2,2	3
STEAM				
Steam valve connection Ø	DN-BSP	15-½"	15-½"	15-½"
Steam pressure	kPa	400-600	400-600	400-600
Steam consumption	kg/cycle	5	7,5	9
AIR				
Air connection Ø	mm	optional / 8	optional / 8	optional / 8
WATER				
Inlet valve connection Ø	DN-BSP	2 x 20-¾"	2 x 20-¾"	2 x 20-¾"
Water inlet (detergent) Ø	DN-BSP	-	-	-
Water pressure	kPa	200-400	200-400	200-400
Water flow	l/min	60	60	140
Water consumption*	cold	l/cycle	39	58
	hot	l/cycle	42	62
Drain valve connection Ø (outer)	mm	76	76	76
Drain flow	l/min	230	230	230
PROGRAMMABLE CONTROL				
16 default programmes (max. 99)		Std	Std	Std
7" colour, high-resolution LCD		Std	Std	Std
DIMENSIONS (WxDxH)				
Standard	mm	880 x 976 x 1500	880 x 1136 x 1500	880 x 1226 x 1500
Standard with plinth	mm	880 x 976 x 1710	880 x 1136 x 1710	880 x 1226 x 1710
Packing	mm	930 x 1040 x 1550	930 x 1200 x 1550	930 x 1300 x 1550
Packing with plinth	mm	930 x 1040 x 1760	930 x 1200 x 1760	930 x 1300 x 1760
WEIGHT				
Net	kg	438	463	476
Net with plinth	kg	460	486	500
Gross	kg	460	488	504
Gross with plinth	kg	525	541	575
SOUND LEVEL				
	db(A)	55-65	55-65	55-65

* Consumption figures based on 'Eco 60°C' program (main wash, 2 rinses)

TOLON reserves the right to make changes to the machines and the specifications in this datasheet at any time, without prior notice. Details and photographs are only for informational purposes and are never binding.

www.tolon.com

TOLON